

DECLARATION OF CONFORMITY

Issued in accordance with the
EUROPEAN STANDARD EN 15283-1: 2008

This is to certify

15mm Glasroc F FIRECASE

15mm Glasroc F RIDURIT

15mm Glasroc F STUCAL

15mm Glasroc F RINOFLAM

Complies with the European Standard and the requirements of the Mandate given under
 EU Construction Products Directive 89/106/EEC.

MS Chaldecott

10/11/08

Signed

Date

Mike Chaldecott
 Managing Director - British Gypsum

EN classification:	GM-F, H2
Longitudinal flexural strength:	645N
Transverse flexural strength:	252N
Reaction to fire:	A1
Water vapour resistance:	10
Thermal conductivity:	0.3W/mK
Shear strength:	NPD

British Gypsum, East Leake, Loughborough, Leicestershire, LE12 6HX



DECLARATION OF CONFORMITY

Issued in accordance with the
EUROPEAN STANDARD EN 15283-1: 2008

This is to certify

20mm Glasroc F FIRECASE

20mm Glasroc F RIDURIT

20mm Glasroc F STUCAL

20mm Glasroc F RINOFLAM

Complies with the European Standard and the requirements of the Mandate given under
 EU Construction Products Directive 89/106/EEC.

MS Chaldecott

10/11/08

Signed

Date

Mike Chaldecott
 Managing Director - British Gypsum

EN classification:	GM-F, H2
Longitudinal flexural strength:	860N
Transverse flexural strength:	336N
Reaction to fire:	A1
Water vapour resistance:	10
Thermal conductivity:	0.3W/mK
Shear strength:	NPD

British Gypsum, East Leake, Loughborough, Leicestershire, LE12 6HX



DECLARATION OF CONFORMITY

Issued in accordance with the
EUROPEAN STANDARD EN 15283-1: 2008

This is to certify

25mm Glasroc F FIRECASE

25mm Glasroc F RIDURIT

25mm Glasroc F RINOFLAM

Complies with the European Standard and the requirements of the Mandate given under
 EU Construction Products Directive 89/106/EEC.

MS Chaldecott

10/11/08

Signed

Date

Mike Chaldecott
 Managing Director - British Gypsum

EN classification:	GM-F, H2
Longitudinal flexural strength:	1075N
Transverse flexural strength:	420N
Reaction to fire:	A1
Water vapour resistance:	10
Thermal conductivity:	0.3W/mK
Shear strength:	NPD

British Gypsum, East Leake, Loughborough, Leicestershire, LE12 6HX



DECLARATION OF CONFORMITY

Issued in accordance with the
EUROPEAN STANDARD EN 15283-1: 2008

This is to certify

30mm Glasroc F FIRECASE

30mm Glasroc F RIDURIT

30mm Glasroc F STUCAL

30mm Glasroc F RINOFLAM

Complies with the European Standard and the requirements of the Mandate given under
 EU Construction Products Directive 89/106/EEC.

MS Chaldecott

Signed

10/11/08

Date

Mike Chaldecott
 Managing Director - British Gypsum

EN classification:	GM-F, H2
Longitudinal flexural strength:	1290N
Transverse flexural strength:	504N
Reaction to fire:	A1
Water vapour resistance:	10
Thermal conductivity:	0.3W/mK
Shear strength:	NPD

British Gypsum, East Leake, Loughborough, Leicestershire, LE12 6HX

